



artivision technologies

EVX Client



> Features

- > Quad screens consoles
 - Management console
 - Event spot monitor
 - Tracking and live spot monitor
 - Interactive site map
- > Administration setup
 - Manages the entire system
 - Add and organized cameras into customizable groups
 - Setup video analytics rules, review videos, set schedules and export videos
- > Support multiple EVX-C connected to EVX-M with user access control management





> EVX Client Specifications

Video Output

- > 4 DVI video output each at 1280px by 1024px

Network, Storage and Video Export

- > 2 RJ45 10/100/1000 Ethernet ports
- > 2 high performance system drive configured as RAID 1
- > Export in AVI files with non-intrusive file authentication protection based on RSA 1024bits encryption
- > Export via USB 2.0 storage devices

Dimensions, Power and Environmental

- > Rackable Minitower (5U)
- > Dimension: 444mm (W) x 525mm (H) x 203mm (D)
- > Gross weight: avg. 21Kg
- > Power input: 100VAC - 240VAC, 50Hz - 60Hz, 11A - 5.5A
- > Peak AC watts: 850W
- > Operating temperature: 5°C to 35°C
- > Operating humidity: 8% to 85% (non-condensing)

> Ordering Information

Product Code	Description	List Price (SGD)
EVX-C	Enterprise Video Client - Manage up to 1024 channels - Quad screen management consoles	

Product specifications and availability subject to change without notice